

## Large Dimension PEX-a Pipes

MrPEX<sup>®</sup> Barrier PEX tubing is Cross-Linked Polyethylene (PEX-a) manufactured in accordance with ASTM F 876.

Tubing is listed to ASTM F 876/877 (CSA B137.5), and also certified by NSF (NSF-rfh).

MrPEX<sup>®</sup> Barrier PEX tubing is rated by the Hydrostatic Stress Board of PPI (Plastics Pipe Institute) at:

- 160 psi at 73.4°F
- 100 psi at 180°F
- 80 psi at 200°F

MrPEX<sup>®</sup> Barrier PEX tubing has an EVOH oxygen barrier that meet DIN 4726.



### DATA

Part#	Coil OD	Coil Width	Weight
1260015	41"	5.8"	35 lbs
1270015	41"	7.2"	50 lbs

### TUBING

Part#	Description	Type	Unit
1260015	MrPEX PEX-a Tubing with Oxygen Barrier	1 1/4"	150 ft Coil
1270015	MrPEX PEX-a Tubing with Oxygen Barrier	1 1/2"	150 ft Coil

### FITTINGS

Part#	Description	Type	Unit
4461313	PEX Transition Assembly, Brass	1 1/4" PEX x 1 1/4" NPT	Each
4461515	PEX Transition Assembly, Brass	1 1/2" PEX x 1 1/2" NPT	Each