


# Product Data Sheet



## MrPEX<sup>®</sup> PEX-a Barrier Tubing

MrPEX<sup>®</sup> Barrier PEX tubing is Cross-Linked Polyethylene (PEX-a) manufactured and listed to ASTM F 876/877 (CSA B137.5).



Third party testing and certification by NSF (NSF-rfh).

Temperature and pressure rated by the Hydrostatic Stress Board of PPI (Plastics Pipe Institute) at:

- 160 psi at 73.4°F
- 100 psi at 180°F
- 80 psi at 200°F

Listed by ICC-PMG 1053.

EVOH oxygen barrier meet DIN 4726. Noise reduction barrier on all sizes up to 3/4".



Compatible with fitting standards ASTM F877, F2080, F1960, F1807

### TUBING

Part#	Description	Type	Unit
1210060	3/8 - Mr PEX Tubing with Oxygen Barrier	600 ft.	Coil
1210100	3/8 - Mr PEX Tubing with Oxygen Barrier	1000 ft.	Coil
1220030	1/2 - Mr PEX Tubing with Oxygen Barrier	300 ft.	Coil
1220050	1/2 - Mr PEX Tubing with Oxygen Barrier	500 ft.	Coil
1220100	1/2 - Mr PEX Tubing with Oxygen Barrier	1000 ft.	Coil
1220120	1/2 - Mr PEX Tubing with Oxygen Barrier	1200 ft.	Coil
1220160	1/2 - Mr PEX Tubing with Oxygen Barrier	1600 ft.	Coil
1230030	5/8 - Mr PEX Tubing with Oxygen Barrier	300 ft.	Coil
1230050	5/8 - Mr PEX Tubing with Oxygen Barrier	500 ft.	Coil
1230110	5/8 - Mr PEX Tubing with Oxygen Barrier	1100 ft.	Coil
1240030	3/4 - Mr PEX Tubing with Oxygen Barrier	300 ft.	Coil
1240040	3/4 - Mr PEX Tubing with Oxygen Barrier	400 ft.	Coil
1240050	3/4 - Mr PEX Tubing with Oxygen Barrier	500 ft.	Coil
1250030	1 - Mr PEX Tubing with Oxygen Barrier	300 ft	Coil
1260015	1 1/4 - Mr PEX Tubing with Oxygen Barrier	150 ft	Coil
1270015	1 1/2 - Mr PEX Tubing with Oxygen Barrier	150 ft	Coil