## Potable PEX-a Tubing



Data Sheet

Radiant Heating & Cooling / Plumbing / Snowmelt / Controls

## Available in Size 1/2" through 2"

• MrPEX® POTABLE PEX-a tubing is offered in  $\frac{1}{2}$ ",  $\frac{3}{4}$ ", 1", 1  $\frac{1}{4}$ ", 1  $\frac{1}{2}$ " and 2"

coils and straight lengths of RED, WHITE and BLUE colors to help identify hot and cold water supply.

colors to help identify not and cold water supply.

•Listed to: ASTM F 876/F877/F2023, ASTM E84 (CSA B137.5), cNSFus-pw, NSF/ANSI-61, NSF/ANSI-14, Annex G, NSF U.P.Code

PEX 5106, ICC-PMG, ANSI/AWWA 904.

•MrPEX<sup>®</sup> POTABLE PEX-a tubing is rated by the Hydrostatic Stress Board of PPI (Plastics Pipe Institute) at: 160 psi at 73.4°F; 100 psi at 180°F.

•MrPEX<sup>®</sup> POTABLE PEX-a tubing may be used with fittings that are compliant with ASTM F1807/F1960/F2080/F2098/F2159 standards.

• MrPEX<sup>®</sup> POTABLE PEX-a tubing carries a 30 year limited warranty.

Potable PEX-a		Available colors			
Size	Unit	Red	White	Blue	Natural
1/2"	Box of 6– 100' coils	Х	Х	Х	
1/2"	300' Coil	Х	X	Х	
1/2"	500' Coil	Х	x	Х	
1/2"	Bag of 20-400' (20' Sticks)	Х	x	Х	
3/4"	Box of 3—100' Coils	Х	X	Х	
3/4"	300' Coil	Х	X	Х	
3/4"	Bag of 10—200' (20' Sticks)	Х	Х	Х	
1"	100' Coil	Х	Х	Х	
1″	300' Coil	Х	x	Х	
1"	Bag of 5– 100' (20' Sticks)	Х	x	Х	
1 1/4"	100' Coil				x
1 1/4"	Bag of 5– 100' (20' Sticks)				x
1 1/2"	100' Coil				x
1 1/2"	Bag of 5– 100' (20' Sticks)				X
2″	100' Coil				X
2″	Bag of 5– 100' (20' Sticks)				X

