PEX-AL-PEX Tubing



Data Sheet

Radiant Heating & Cooling / Plumbing / Snowmelt / Controls

Available in Size 1/2" through 1"

- •MrPEX® PEX-AL-PEX tubing is a 5 layer composite pipe manufactured to ASTM F 1281-2005 (CSA B137.10).
- Certified by NSF (NSF-rfh)
- •Temperature/pressure rated by the Hydrostatic Stress Board of PPI (Plastics Pipe Institute) in accordance with ASTM F 1281-2005 (CSA B137.10) to 160 psi at 200°F
- •The tubing has an expansion coefficient almost 9 times less than regular PEX. Noise and movement after installation is virtually eliminated.
- •The tubing has an expansion coefficient almost 9 times less than regular PEX. Noise and movement after installation is virtually eliminated.
- •Aluminum core is 100% gas/oxygen tight



Size	OD	Wall	ID
1/2"	0.630	0.065	0.500
5/8"	0.787	0.075	0.637
3/4"	0.984	0.089	0.806
1"	1.260	0.118	1.024

Size	Part #	Туре
1/2"	1320025	250 ft White Coil
1/2"	1320030	300 ft White Coil
1/2"	1320100	1000 ft White Coil
5/8"	1220120	400 ft White Coil
5/8"	1220160	500 ft White Coil
3/4"	1230030	300 ft White Coil
3/4"	1230033	500 ft White Coil
1"	1230050	100 ft White Coil
1"	1230100	300 ft White Coil
1"	1230110	500 ft White Coil