

PEX-a Barrier Tubing

Radiant Heating & Cooling / Plumbing / Snowmelt / Controls

Available in Size 3/8" through 2"

- MrPEX® PEX-a Barrier Tubing is offered in 3/8", 1/2", 5/8", 3/4", 1", 1-1/4", 1-1/2" and 2" coils and straight lengths
- Listed to: ASTM F 876/F877(CSA B 137.5) DIN 4726
- MrPEX® PEX-a Barrier Tubing is rated by the Hydrostatic Stress Board of PPI (Plastics Pipe Institute) at: 160 psi at 73.4°F; 100 psi at 180°F.
- MrPEX® PEX-a Barrier Tubing may be used with fittings that are compliant with ASTM F1807/F1960/F2080/F2159 standards.
- MrPEX® PEX-a Barrier Tubing carries a 30 year limited warranty.



Size	Part #	Type
3/8"	1210060	600 ft Coil
3/8"	1210100	1000 ft Coil
3/8"	1210240	2400 ft Coil
1/2"	1220030	300 ft Coil
1/2"	1220050	500 ft Coil
1/2"	1220100	1000 ft Coil
1/2"	1220120	1200 ft Coil
1/2"	1220160	1600 ft Coil
5/8"	1230030	300 ft Coil
5/8"	1230033	330 ft Coil
5/8"	1230050	500 ft Coil
5/8"	1230100	1000 ft Coil
5/8"	1230110	1100 ft Coil

Size	Part #	Type
3/4"	1240010	100 ft Coil
3/4"	1240030	300 ft Coil
3/4"	1240040	400 ft Coil
3/4"	1240050	500 ft Coil
3/4"	1240100	1,000 ft Coil
3/4"	1241020	Bag of 10-20 ft Sticks
1"	1250010	100 ft Coil
1"	1250030	300 ft Coil
1"	1251020	Bag of 10-20 ft Sticks
1 1/4"	1260015	150 ft Coil
1 1/4"	1261010	Bag of 5-20 ft Sticks
1 1/2"	1270015	150 ft Coil
1 1/2"	1271010	Bag of 5-20 ft Sticks
2"	1280020	200 ft Coil
2"	1281010	Bag of 5-20 Sticks