

# PEX-a Oxygen Barrier Tubing

Radiant Heating & Cooling / Plumbing / Snowmelt / Controls

## Available in Size 3/8" through 2"

- MrPEX<sup>®</sup> PEX-a Oxygen Barrier Tubing is offered in 3/8", 1/2", 5/8", 3/4", 1", 1-1/4", 1-1/2" and 2" coils and straight lengths
- Listed to: ASTM F 876/F877(CSA B 137.5) DIN 4726
- MrPEX<sup>®</sup> PEX-a Oxygen Barrier Tubing is rated by the Hydrostatic Stress Board of PPI (Plastics Pipe Institute) at: 160 psi at 73.4°F; 100 psi at 180°F.
- MrPEX<sup>®</sup> PEX-a Oxygen Barrier Tubing may be used with fittings that are compliant with ASTM F1807/F1960/F2080/F2159 standards.
- MrPEX<sup>®</sup> PEX-a Oxygen Barrier Tubing carries a 30 year limited warranty.



| Size | Part #  | Type         |
|------|---------|--------------|
| 3/8" | 1210060 | 600 ft Coil  |
| 3/8" | 1210100 | 1000 ft Coil |
| 3/8" | 1210240 | 2400 ft Coil |
| 1/2" | 1220030 | 300 ft Coil  |
| 1/2" | 1220050 | 500 ft Coil  |
| 1/2" | 1220100 | 1000 ft Coil |
| 1/2" | 1220120 | 1200 ft Coil |
| 1/2" | 1220160 | 1600 ft Coil |
| 5/8" | 1230030 | 300 ft Coil  |
| 5/8" | 1230033 | 330 ft Coil  |
| 5/8" | 1230050 | 500 ft Coil  |
| 5/8" | 1230100 | 1000 ft Coil |
| 5/8" | 1230110 | 1100 ft Coil |

| Size   | Part #  | Type                   |
|--------|---------|------------------------|
| 3/4"   | 1240010 | 100 ft Coil            |
| 3/4"   | 1240030 | 300 ft Coil            |
| 3/4"   | 1240040 | 400 ft Coil            |
| 3/4"   | 1240050 | 500 ft Coil            |
| 3/4"   | 1240100 | 1,000 ft Coil          |
| 3/4"   | 1241020 | Bag of 10-20 ft Sticks |
| 1"     | 1250010 | 100 ft Coil            |
| 1"     | 1250030 | 300 ft Coil            |
| 1"     | 1251020 | Bag of 10-20 ft Sticks |
| 1-1/4" | 1260015 | 150 ft Coil            |
| 1-1/4" | 1261010 | Bag of 5-20 ft Sticks  |
| 1-1/2" | 1270015 | 150 ft Coil            |
| 1-1/2" | 1271010 | Bag of 5-20 ft Sticks  |
| 2"     | 1280020 | 200 ft Coil            |
| 2"     | 1281010 | Bag of 5-20 Sticks     |