

Radiant Wood Track

Radiant Heating & Cooling / Plumbing / Snowmelt / Controls

MrPEX® Radiant Wood Track is a low-profile radiant floor heating underlayment designed for both retrofit and new construction in residential and commercial applications. Compatible with all hydronic heating systems, it also pairs well with low-temperature heat sources such as geo-thermal heat pumps and high-efficiency boilers. The system includes three 12" x 48" panel types: **Run**, **Turn-Around**, and **Manifold**. Each panel is marked for easy cutting and layout customization. A typical installation uses approximately **80% Run Panels** and **20% Turn-Around Panels**.



Run Panel
#6115019



Turn-around Panel
#6115029



Manifold Panel
#6115039



Specifications:	
Panel Thickness	5/8"
Panel Dimensions	12" x 48"
Panel Weight	6.67 lbs
Plywood Type	CCX-Formaldehyde Free 5 ply Exterior Grade
Tubing Size	3/8" PEX
Tube Spacing	6" On Center
Heat Transfer	Convection / Conduction

Part #	Description	Type	Unit
6115019	Radiant Wood Track for 3/8" Pex Tubing, 12" x 48"	Run Panel—6" O.C.	Box of 10
6115029	Radiant Wood Track for 3/8" Pex Tubing, 12" x 48"	Turn-Around Panel—6" O.C.	Box of 10
6115039	Radiant Wood Track for 3/8" Pex Tubing, 12" x 48"	Manifold Panel—6" O.C.	Box of 10
6115049	Radiant Wood Track for 3/8" Pex Tubing, 12" x 48"	Manifold Panel—6" O.C.	Each